

PERFECT FIT VENETIAN BLINDS

	RAINBOW STANDARD	OPTIONS
System	Louvolite Perfect Fit	n/a
Slat Size	25mm	n/a
Control	Tension	Cord
Control Side	None	Right hand side, Left hand side
Bracket	PF brackets	Please specify 20, 22, 24, 30, 38mm to suit bead depth
Frame	White	Anthracite Grey, Brown, Golden Oak, Grey, Mahogany
Endset & Window Corner Cover	White	Anthracite Grey, Brown, Grey, Tan
Child Safety	n/a	Cord Tidy (anthracite grey, brown, White)
Minimum Control Length	150mm	n/a
Measuring Method	Glass	n/a

ADDITIONAL INFORMATION:

- Width: 275mm – 1500mm (maximum width 1400mm for tensioned)
- Drop: 200mm – 2000mm
- Tensioned as standard. Corded system
- Frame side channel: 38mm width; 26mm depth
- Specify bracket size when ordering
- Actual glass size only measurements accepted
- Window handle spacers available in 2mm and 6mm
- Backing Foam for frame (white only)
- Konnect Magnetic Tape is not suitable for chain operated blind.
- Rebate handle available in Anthracite Grey, Black, Brown, Tan, White. Specify rebate handle location when ordering
- Additional cost for Golden Oak and Mahogany frame.

PERFECT FIT ROLLER BLINDS

	RAINBOW STANDARD	OPTIONS
System	Louvolite Perfect Fit	n/a
Roller Tube	Aluminium	n/a
Finish	No-sew, wraparound	Exposed
Control	Sidewinder	Spring or motorised
Operating Chain	White	Anthracite Grey, Brown, Grey, Tan
Control Side	Right hand side	Left hand side, None
Bracket	PF brackets	Please specify 18, 20, 22, 24, 30, 38mm to suit bead depth
Frame	White	Anthracite Grey, Brown, Golden Oak, Grey, Mahogany
Endset & Window Corner Cover	White	Anthracite Grey, Brown, Grey, Tan
Child Safety	Cord tidy (White)	Motorisation, Cord Tidy (anthracite grey, brown)
Minimum Control Length	150mm	n/a
Measuring Method	Glass	n/a

ADDITIONAL INFORMATION:

- Width: 350mm – 1400mm
- Drop: 200mm – 2000mm (minimum 500mm drop for Chain Control)
- Maximum Area: up to 2.8m² (depending on the fabric)
- Max Drops by widths:
 - width < 400mm – max drop = 1100mm
 - width < 500mm – max drop = 1700mm
 - width < 600mm – max drop = 1900mm
 - width > 600mm – max drop = 2000mm
- Chain Control as standard. Tensioned available upon request at no extra cost
- Chain length is minimum 400mm endless loop
- Motorisation available with Somfy and Louvolite options. See page 94
- Perfect Fit Roller Curved Extrusion: 74mm height; 58mm depth
- End Set Cover: 97mm height; 75mm width
- Frame side channel: 38mm width; 26mm depth
- Specify bracket size when ordering
- Actual glass size only measurements accepted
- Hinged Handle colour options: Anthracite Grey, Black, Brown, Tan, White
- Folding Handle option
- Window handle spacers available in 2mm and 6mm
- Backing Foam for frame (white only)
- Konnect Magnetic Tape is not suitable for chain operated blind.
- Rebate handle available in Anthracite Grey, Black, Brown, Tan, White. Specify rebate handle location when ordering
- Additional cost for Golden Oak and Mahogany frame

PERFECT FIT PLEATED BLINDS

	RAINBOW STANDARD	OPTIONS
System	Louvolite Perfect Fit	Louvolite Perfect Fit International (PFI)
Headrail	20mm	n/a
Control	Tension	n/a
Control Options	Manual operating handle	Detached 2m Operating wand with twist lock
Bracket	PF brackets	Please specify 18, 20, 22, 24, 30, 38mm to suit bead depth. All PFI come with Standard Roof Fixing Bracket for 12-22mm bead depth.
Frame	White	Anthracite Grey, Brown, Golden Oak, Grey, Mahogany
Headrail	White	Anthracite Grey, Brown, Silver, Tan
Headrail End Caps	White	Brown, Light Grey
Intermediate Rail & End Caps	White	Brown
Window Corner Cover	White	Anthracite Grey, Brown, Grey, Tan
Child Safety	'Safe by design' and comply with BS EN 13120.	n/a
Measuring Method	Glass	n/a
Angled Shapes	n/a	Roof & Side Blinds only with Perfect Fit International

ADDITIONAL INFORMATION:

- Perfect Fit Pleated
 - Width: 100mm – 1400mm
 - Drop: 200mm – 2000mm
 - Max area: 2.8m²
- Perfect Fit International + £30 surcharge
 - Width: 100mm – 1000mm
 - Drop: 200mm – 3000mm
 - Max area: 3m²
 - Only available in White and Brown
 - Plastic sheets to cover angled corners – Apex and Flat Corner (50°, 70°, 90°, 110°, 135°)
- PF International Shape
- PF Pleat Frame side channel: 38mm width; 26mm depth
- PF Pleat headrail 20mm
- Specify bracket size when ordering (PF Pleated only)
- Perfect Fit International Standard bracket (Flush fitting) cover bead depths from 12-22mm and Multiroof bracket (Recess fitting) covers over 22mm. Specify Multiroof when ordering.
- Actual glass size only measurements accepted
- Folding Handle colour options: Anthracite Grey, Black, Brown, Light Grey, Tan, White (standard)
- Window handle spacers available in 2mm and 6mm
- Backing Foam for frame (white only)
- Konnect Magnetic Tape is not suitable for chain operated blind.
- Rebate handle available in Anthracite Grey, Black, Brown, Tan, White. Specify rebate handle location when ordering
- Additional charge for Golden Oak and Mahogany frame.
- Detachable Operating Wand