

## ALUMINIUM VENETIAN BLINDS

	RAINBOW STANDARD	OPTIONS
Slat Size	n/a	25, 35 or 50mm
Headrail	Colour co-ordinated	n/a
Bottom Bar	Colour co-ordinated	n/a
Ladder	Colour co-ordinated	n/a
Cord	Colour co-ordinated	n/a
Raise Control	Right hand side cord	Left hand side cord
Tilt Control	Left hand side cord	Right hand side cord, Wand
Brackets	Universal Swivel brackets	Extension or End Fix
Child Safety	Breakaway cord condenser and 2-piece cleat	Motorisation
Minimum Control Length	150mm	n/a
Control Length Deduction from floor with Fitting Height	1500mm	n/a
Measuring Method	Recess	Exact Blind Size

**ADDITIONAL INFORMATION:**

- Width: 275mm – 3800mm
- Drop: 350mm – 3000mm
- 25 mm Ultimate System
- 25mm x 25mm headrail with chamfered edges
- Slim 20mm bottom rail – fully enclosed
- Industry High 25-micron Alloy 6011 slatting for durability and bounce back quality
- Moulded polypropylene components for smoothness and durability
- Colour matching head rail, bottom rail and cords. See following pages for full list
- Raise and tilt controls can be on same side depending on size. Ask Sales Team to confirm
- Motorisation via Somfy Tilt & Lift control is available. See page 94 for motorisation specification
- Standard webbing is 25mm; 18mm option is available. Specify this when ordering
- Privacy Option
- Side Guide Option
- Partition Option
- Hold Down Brackets
- Extension Brackets

## INTU VENETIAN BLINDS

	RAINBOW STANDARD	OPTIONS
System	Intu Venetian Bead Fit	Intu Venetian Screw Fit
Slat	25mm	n/a
Control	Top control slat tilter	Wand operation
Bracket	Intu brackets	Please specify to suit bead depth (11mm-27mm)
Rail	White	Anthracite Grey, Brown
Child Safety	'Safe by design' and comply with BS EN 13120.	n/a
Measuring Method	Glass	n/a
Finish	Standard	Privacy

### ADDITIONAL INFORMATION:

- Bead Fit Width: 230mm – 1400mm
- Screw Fit Width: 240mm – 1500mm
- Drop: 100mm – 2500mm (Beadfit to 2000mm)
- Max Area:
  - Beadfit: 1.5m<sup>2</sup>
  - Screw Fit 2.5m<sup>2</sup>
- 25mm slat as standard
- Anthracite Grey, Brown, and Silver rail colours + 10% surcharge
- Bead Fit:
  - Blind width = Glass size – 2mm
  - Blind drop = Glass size
  - Side Extrusions = Blind drop – 9mm
  - Headrail = Glass size + 63mm
  - Bottom rail = Blind Width – 20mm
- Screw fit:
  - Blind width = Glass size – 2mm
  - Blind drop = Glass size
  - Headrail = Blind width
  - Bottom rail = Blind Width – 10mm
- Top Control Tilter located in centre of headrail
- Wand operation available for tilting
- Specify Bead Depth and Profile upon ordering